## **AUTOMATIC CHARGE DISCHARGE TESTER (5000Amps)**



## **Features**

- Manual Loading of the Test Capacitor to the Test fixture.
- Capacitance Range from 1mfd to 500mfd.
- Adjustable Test Voltage through Salzer Switch provided on Front Panel.
- Adjustable Current From 100A to 10, 000A.
- Adjustable Charge Discharge Time through Text Panel interfaced to PLC.
- Monitoring of charge discharge slopes through oscilloscopes output.
- Voltage accuracy ±3%
- Current Accuracy ±10%
- Discharge Through Vacuum Circuit Breaker.

## **Technical Specification**

Test Voltage	600 to 1500 V DC.
Voltage Indication	3½ digit Digital Voltmeter.
Current	100 to 10,000 A.
Test Capacitance Range	1 to 500 MFD.
Charge Time	Adjustable 1 to 5 Sec.
Discharge Time	Adjustable 0.3 to 1Sec.
No. Of Test Cycles	Programmable On Digital Counter up to 10,000.
Digital Counter	6 Digit Up & Down Counter.
Indicators	Power ON & OFF, Test Over & Alarm.



## **General Specification**

Power Supply : 230V AC, 50Hz, 1 ph. Machine weight : 18Kgs.(Approx.)

Floor space : 450 x 465 x 266 mm (W x L x H). Air Supply : 6 bars, Consumption 4 cfm.

NOTE: We reserve the right to modify above specifications at any time. please confirm your specification before ordering.