

AUTOMATIC WIRE CUTTING AND STRIPPING MACHINE (DUAL FEED)



Features

- ❑ The machine is designed for single/multi strand wire cutting for pre set length and stripping both ends automatically for pre set length.
- ❑ It includes Digital LCD display & controlling keypad.
- ❑ Parameters with different settings can be stored. Total 100 programs can be stored in memory for selection.
- ❑ Total production quantity can be pre set.
- ❑ The number of wires required for bundling (Knot Quantity) can be preset in the program automatically. Also time required for bundling can be set by giving required delay time.
- ❑ Dual wire feed for cutting and stripping, increases productivity.

Technical Specification

Model	WCS25D
Cable Wire	0.1 sqmm - 2.5 sqmm.
Cutting Length	Continuously Programmable from 50mm to 9999mm in steps of 1mm
Cutting Tolerance (LEN)	$\leq (0.002 \times L) \text{mm}$ (L=Cutting Length)
Stripping Length	Head: 0 - 15mm, Tail: 0 - 15mm.
Stripped Wire Peeling Length	Head: 0 - 15mm, Tail: 0 - 15mm.
Memory	Total 100 Programs.
Speed (SPD)	10 Selectable Speed (0 - 9)
Amount (AMT)	Total Production Quantity (0 - 9999)
Total (TOT)	Required Production Quantity (0 - 9999)
Group (GRP)	Quantity per bunch (0 - 9999)
Delay (DLY)	0 - 9 seconds
Display	Digital LCD display with control switches.
Production Capacity	3000 to 5000 Pc/Hour
Weight	31 Kgs (Approx.)

